



FEATURES	24L-340D	24L-235
Item Management		
Total Items for Check Out	340	235
Standard Slot Dimensions (Imperial) (Metric)	12.5h x 8.25d x 1.6 Spine 318h x 210d x 42 Spine	
Items in Standard Slots	268	188
Wide Slot Dimensions (Imperial) (Metric)	12.5h x 8.25d x 2.4 Spine 318h x 210d x 62 Spine	
Items in Wide Slots	67	47
Hold Drawer Dimensions (Imperial) (Metric)	10.35d x 13.7w 1.9h 348.6w x263.5d x 49h	N/A N/A
Items in Hold Drawers	5	N/A
Item Return Capacity	1000	600
Sorter Return Bins	14	9
RFID Item	Standard	
Barcode Item	Standard	
Patron Interfaces		
Primary Screen Interface	17" High Brightness Resistive Industrial Color Touch Screen	
ADA Screen Interface	5.6" Standard Industrial Resistive Color Touch Screen	
Operating Systems	Windows 10 Professional	Window 10 Professional
Main System Computer	E5300 2.6Ghz Dual Core 4GB RAM, 10-RS232, 6-USB, 250GB SSD	J1900 2.6Ghz Quad Core 4GB RAM, 5-RS232, 8-USB, 120GB SSD
Right Display	43" 1000nit Infrared Touch Screen Display - Portrait	
Right Display Computer	J1900 2.6Ghz Dual Core 4GB RAM, 5-RS232, 8-USB, 120GB SSD	J1900 2.6Ghz Dual Core 4GB RAM, 5-RS232, 8-USB, 120GB SSD
Left Display	32" Touch Screen Display - Landscape	N/A
Left Display Computer	J1900 2.6Ghz Dual Core 4GB RAM, 5-RS232, 8-USB, 120GB SSD	N/A
RFID Patron Card	Standard	
Barcode Patron Card	1D/2D Smartphone-Ready Patron Card Barcode Reader	
Receipt	High Capacity 80mm	

Specifications subject to change without notice.



FEATURES	24L-340D	24L-235
----------	----------	---------

## Connectivity

ILS Connection	SIP2   Enhanced SIP2 for 24-Library*	
ILS Configuration	Remote Site: Branch   Outside Library Building: Shelf Location	
System Ethernet Connection	RJ-45	
Library Device Support	Power Strip and Mounting Space for WAN Modem/Connect Device	
Router	2-Channel Wi-Fi   LAN   VPN   Configurable Content Filtering	

## Protection

DVR	30-day DVR - Remotely Accessible	
Security Cameras	5 Cameras	4 Cameras

## Mechanical

Dimensions (Imperial)	13.23w x 7.5h x 5.68d	9.84w x 7.05h x 4.92d
(Metric)	4032w x 2286h x 1730d	3000w x 2149h x 1500
Overall Size Comparison	Model 235 is 55% of the size of Model 340D	
Weight	7055 lbs   3200kg	5380 lbs   2440kg
Temperature without Heat	-5° to 125°F   -15° to 52°C	
with Heat	-20° to 125°F   -29° to 52°C	

## Power

Power For System	(1) 120V 20A Circuit	
Power For Heat Systems	(3) 120V 20A Circuits	
Power Consumption Without Heat	1200W	1000W
Power Consumption With Heat	7200W	7000W
Warranty	One Year Remote and Onsite 24x7x365 Support	
On-Site Maintenance After Year 1	Yes	

## Options

Project Management, Installation and Training  
Construction Guidance  
API Integration  
Credit Card Payment Terminal  
Fine/Fee Payment Software

Computer Management Client  
Canopy for Standard Op Temps  
Uninterruptable Power Supply  
220V / 50Hz